



Diavel 1260

Motore / Engine	Testastretta DVT 1262, V2 a 90°, 4 valvole per cilindro, Desmodromic Variable Timing, Dual Spark, raffreddamento a liquido / Testastretta DVT 1262, V2 - 90°, 4 valves per cylinder, Desmodromic Variable Timing, Dual Spark, liquid cooled
Cilindrata / Displacement	1.262 cc / 1,262 cc (77.0 cu in)
Potenza / Power	162 CV (119 kW) @ 9.500 giri/min / 162 hp (119 kW) @ 9,500 rpm* - 157 hp (116 kW) @ 9,250 rpm** - 159 hp (117 kW) @ 9,500 rpm***
Coppia / Torque	13,2 kgm (129 Nm) @ 7.500 giri/min / 13.2 kgm (129 Nm, 95 lb ft) @ 7,500 rpm
Telaio / Frame	Traliccio in tubi di acciaio / Tubular steel trellis frame
Sospensione anteriore / Front suspension	Forcella a steli rovesciati regolabile Ø50 mm / Adjustable Ø50 mm usd fork
Pneumatico anteriore / Front tyre	Pirelli Diablo Rosso III 120/70 ZR17
Sospensione posteriore / Rear suspension	Monoammortizzatore regolabile in precarico ed estensione, forcellone monobraccio fuso in alluminio / Preload and rebound adjustable monoshock, single-sided aluminium cast swingarm
Pneumatico posteriore / Rear tyre	Pirelli Diablo Rosso III 240/45 ZR17
Freno anteriore / Front brake	2 dischi semiflottanti Ø320 mm, pinze Brembo monoblocco M4.32 ad attacco radiale a 4 pistoncini, pompa radiale PR18/19, ABS Cornering / 2 x Ø320 mm semifloating discs, radial mounted Brembo monobloc 4-piston M4.32 callipers, PR18/19 radial master cylinder, Cornering ABS
Freno posteriore / Rear brake	Disco Ø265 mm, pinza flottante Brembo a 2 pistoncini, ABS Cornering / Ø265 mm disc, Brembo 2-piston floating calliper, Cornering ABS
Peso a secco / Dry weight	223 kg / 223 kg (492 lb)
Peso in ordine di marcia / Weight in running order	249 kg / 249 kg (549 lb)
Altezza sella / Seat height	780 mm / 780 mm (30.7 in)
Capacità serbatoio carburante / Fuel tank capacity	17 l / 17 l (4.5 US gal) - 16 l (4.2 US gal)**
Equipaggiamento di sicurezza / Safety equipment	Riding Mode, Power Mode, ABS Cornering, Ducati Traction Control, Ducati Wheelie Control, Impianto luci full-LED / Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Full-LED lighting system
Equipaggiamento di serie / Standard equipment	Ducati Power Launch, Cruise control, Hands-free, Pulsanti al manubrio retro-illuminati, Display TFT a colori da 3,5" / Ducati Power Launch, Cruise control, Hands-free, Backlit handlebar switches, 3.5" TFT colour display
Predisposizione / Ready for	Ducati Quick Shift, Ducati Multimedia System / Ducati Quick Shift, Ducati Multimedia System
Emissioni e consumi / Emissions and consumption*	Standard Euro 5 - Emissioni CO ₂ 129 g/km - Consumi 5,5 l/100 km / Euro 5 Standard - CO ₂ Emissions 129 g/km - Consumption 5.5 l/100 km

*Solo per paesi dove vige la normativa Euro 5. / Only for countries where Euro 5 standard applies.

**Only for US, Canada and Mexico.

***Other countries.



Diavel 1260 S

Motore / Engine	Testastretta DVT 1262, V2 a 90°, 4 valvole per cilindro, Desmodromic Variable Timing, Dual Spark, raffreddamento a liquido / Testastretta DVT 1262, V2 - 90°, 4 valves per cylinder, Desmodromic Variable Timing, Dual Spark, liquid cooled
Cilindrata / Displacement	1.262 cc / 1,262 cc (77.0 cu in)
Potenza / Power	162 CV (119 kW) @ 9.500 giri/min / 162 hp (119 kW) @ 9,500 rpm* - 157 hp (116 kW) @ 9,250 rpm** - 159 hp (117 kW) @ 9,500 rpm***
Coppia / Torque	13,2 kgm (129 Nm) @ 7.500 giri/min / 13.2 kgm (129 Nm, 95 lb ft) @ 7,500 rpm
Telaio / Frame	Traliccio in tubi di acciaio / Tubular steel trellis frame
Sospensione anteriore / Front suspension	Forcella Öhlins a steli rovesciati regolabile Ø48 mm con trattamento TiN / Öhlins fully adjustable Ø48 mm usd fork with TiN treatment
Pneumatico anteriore / Front tyre	Pirelli Diablo Rosso III 120/70 ZR17
Sospensione posteriore / Rear suspension	Monoammortizzatore Öhlins completamente regolabile, forcellone monobraccio fuso in alluminio / Öhlins fully adjustable monoshock, single-sided aluminium cast swingarm
Pneumatico posteriore / Rear tyre	Pirelli Diablo Rosso III 240/45 ZR17
Freno anteriore / Front brake	2 dischi semiflottanti Ø320 mm, pinze Brembo monoblocco M50 ad attacco radiale a 4 pistoncini, pompa radiale PR16/19, ABS Cornering / 2 x Ø320 mm semifloating discs, radial mounted Brembo monobloc 4-piston M50 callipers, PR16/19 radial master cylinder, Cornering ABS
Freno posteriore / Rear brake	Disco Ø265 mm, pinza flottante Brembo a 2 pistoncini, ABS Cornering / Ø265 mm disc, Brembo 2-piston floating calliper, Cornering ABS
Peso a secco / Dry weight	221 kg / 221 kg (487 lb)
Peso in ordine di marcia / Weight in running order	247 kg / 247 kg (544 lb)
Altezza sella / Seat height	780 mm / 780 mm (30.7 in)
Capacità serbatoio carburante / Fuel tank capacity	17 l / 17 l (4.5 US gal) - 16 l (4.2 US gal)**
Equipaggiamento di sicurezza / Safety equipment	Riding Mode, Power Mode, ABS Cornering, Ducati Traction Control, Ducati Wheelie Control, Impianto luci full-LED, Daytime Running Light / Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Full-LED lighting system, Daytime Running Light****
Equipaggiamento di serie / Standard equipment	Sospensioni Öhlins completamente regolabili, Ducati Power Launch, Cruise control, Hands-free, Pulsanti al manubrio retro-illuminati, Display TFT a colori da 3,5", Ducati Quick Shift, Ducati Multimedia System / Fully adjustable Öhlins suspension, Ducati Power Launch, Cruise control, Hands-free, Backlit handlebar switches, 3.5" TFT colour display, Ducati Quick Shift, Ducati Multimedia System
Emissioni e consumi / Emissions and consumption*	Standard Euro 5 - Emissioni CO ₂ 129 g/km - Consumi 5,5 l/100 km / Euro 5 Standard - CO ₂ Emissions 129 g/km - Consumption 5.5 l/100 km

*Solo per paesi dove vige la normativa Euro 5. / Only for countries where Euro 5 standard applies.

**Only for US, Canada and Mexico.

***Other countries.

****Please check with your dealer feature availability.